

Filter Housings



Pumpmasters range of Filter Housings are available in two lengths: 10 or 20", larger on request. All housings are supplied with a wall mounting bracket, spanner and air bleed screw.

	Port size:	Max. Pressure	Dimensions (mm)
10" SX Single Bowl	¾" BSP	8.0 Bar	134 x 315
20" SX Single Bowl	¾" BSP	8.0 Bar	134 x 570
10" SX Double Bowl	¾" BSP	8.0 Bar	270 x 315
20" SX Double Bowl	1" BSP	8.0 Bar	270 x 570
10" BB Single Bowl	1" BSP	8.3 Bar	190 x 360
20" BB Single Bowl	1½" BSP	8.3 Bar	190 x 620

SX housings are suitable for use with 9 7/8, 10 or 20" cartridges, 3.1" diameter, with either DOE, or Seal Safe O ring sealing. Double bowls allow a mixture of cartridges to be used.

BB housings are suitable for use with higher flow 10 or 20" cartridges, 4.5" diameter, with either DOE, or Seal Safe O ring sealing.

CAUTION: Protect against freezing to prevent cracking of the filter and water leakage



PUMPMASTERS LTD

UNIT 14A, NASMYTH COURT
HOUSTOUN IND. ESTATE
LIVINGSTON, EH54 5EG
SCOTLAND, UK

TEL : 01506 668740
FAX : 01506 668741