

# BB High Flow Filter Housings

The Pumpmasters range of BB High Flow Filter Housings are available in two lengths: 10 or 20 ". Both housings are normally supplied with blue bowls, (clear bowls available to special order).

Port sizes:     10BB - 1" BSP  
                  20BB - 1½" BSP

The housings are suitable for use with 10BB or 20BB sediment, or carbon cartridges, 4.5" diameter, with either DOE, or Seal Safe O ring sealing.



Model	Part Number	Maximum Dimensions	Initial ΔP @ Flow Rate
10BB	66-25H-10BB	333 x 184 mm	0.1 bar @ 57 L/M
20BB	66-38H-10BB	606 x 184 mm	0.1 bar @ 76 L/M

## Materials of Construction

- *Housing:* Polypropylene
- *Cap:* Polypropylene
- *Button Assembly:* Stainless Steel, Polypropylene and EPDM
- *O-Ring:* Buna-N
- *Maximum Temperature:* 37.8°C
- *Maximum Pressure:* 10BB: 6.90 Bar, 20BB: 6.2 Bar

CAUTION: Protect against freezing to prevent cracking of the filter and water leakage



## **PUMPMASTERS LTD**

Unit 14A, Nasmyth Court,  
Houston Industrial Estate, Livingston  
West Lothian, EH54 5EG  
SCOTLAND, UK

TEL: 0131 661 3982